

Hydraulic Access System Ordering Chart

Hydraulic Access Fitting Body Options:

Mounting Options:

1 -	Flare Weld
2 -	Butt Weld
3 -	Socket Weld
4 -	NPT
5 -	2" ANSI Flange RJ
6 -	2" ANSI Flange RF
7 -	2" API Flange RJ
8 -	4" ANSI Flange RF
Z -	Other (custom)

Body Style:

0 0 -	Non-Tee
0 1 -	1/4" Tee
0 2 -	1/2" Tee
0 3 -	3/4" Tee
0 4 -	1" Tee
0 5 -	1/2" 150# RF
0 6 -	1/2" 300# RF
0 7 -	1/2" 4/600# RF
0 8 -	1/2" 9/1500# RF
0 9 -	1/2" 2500# RF
1 0 -	1/2" 150# RJ
1 1 -	1/2" 300# RJ
1 2 -	1/2" 4/600# RJ
1 3 -	1/2" 9/1500# RJ
1 4 -	1/2" 2500# RJ
1 5 -	1" 9/1500# RJ
1 6 -	1" 2500# RJ
1 7 -	3/4" 9/1500# RJ
1 8 -	1" 150# RF
1 9 -	Tee 1/2" & 3/4" (for blank)
Z 0 -	Other (custom)

Pipeline Size:

Flareweld:		
0 -	(Blank)	
1 -	2"	
2 -	3"	
3 -	4"	
4 -	6"	
5 -	8" - 10"	
6 -	12" - 18"	
7 -	20" - 36"	
8 -	Flat	
9 -	38" - 48"	
S -	With Skirt	
Z -	Other (custom)	
ANSI Flange Size:		
0 -	N/A	
1 -	150#	
2 -	300#	
3 -	4/600#	
4 -	9/1500#	
5 -	2500#	
Z -	Other (custom)	
API Flange Size:		
0 -	N/A	
1 -	2000#	
2 -	3/5000#	
3 -	10,000#	
Z -	Other (custom)	

Body Material:

1 -	AISI 1018 Carbon Steel
2 -	ASTM A105 Carbon Steel
3 -	ASTM A350 LF2 Carbon Steel
4 -	ASTM A182 F316/316L
5 -	ASTM A182 F51 (2205)
6 -	ASTM A694 F60
7 -	ASTM A182 F321
8 -	ASTM B564 UNS N10276 (C276)
9 -	ASTM B564 UNS N06625 (I625)
A -	ASTM A182 F44 (254SMO)
B -	ASTM 182 F304L
C -	ASTM A182 F53 (2507)
D -	ASTM B564 UNS N08825 (I825)
E -	ASTM 182 F55 (ZERON 100)
F -	ASTM A182 F51 (2205) CLAD C276
G -	ASTM B348 UNS R50400 (TIGR2)

HF X X X X X X X X X X

Plug Body Type:

0 -	Not Required
1 -	Solid Plug
2 -	Hollow Plug
Z -	Other (custom)

Plug Body Material:

0 -	Not Required
1 -	316
2 -	316L
3 -	C276
4 -	NIT60
5 -	Carbon Steel
6 -	2205 Duplex SS
7 -	I625
8 -	I825
Z -	Other (custom)

Plug Packing Material:

0 -	Not Required
1 -	PTFE (Teflon®)
2 -	SP Polyimide (VespeI®)
3 -	NIT60
Z -	Other (custom)

Cover Body Type:

0 -	Not Required
1 -	Non-Pressure Rated, Without hole
2 -	Non-Pressure Rated, With hole
3 -	6000 PSI, Without Hole
4 -	6000 PSI, Without Hole, Bleed Valve
5 -	6000 PSI, Without Hole, Pressure Gauge
6 -	6000 PSI, Without Hole, Bleed Valve & Gauge
7 -	6000 PSI, 1/2" NPT
8 -	6000 PSI, 1/2" NPT, Bleed Valve
A -	6000 PSI, 1/2" NPT, Pressure Gauge
B -	6000 PSI, 1/2" NPT, Bleed Valve & Gauge
C -	Heavy, Fire Safe (6000 PSI, fire proof seal)
Z -	Other (custom)

Cover Body Material:

0 -	Not Required
1 -	AISI 1018 Carbon Steel
2 -	ASTM A105 Carbon Steel
3 -	ASTM A350 LF2 Carbon Steel
4 -	AISI 316/316L Stainless Steel
5 -	Duplex Stainless Steel
6 -	ASTM A694
7 -	321 Stainless Steel
8 -	C276
Z -	Other (custom)

Hydraulic Plug Assembly Options:

Cover Options:

Metal Samples Company

E-mail: msc@alspi.com Internet: www.metalsamples.com