

Hydraulic Protective Covers


for High Pressure Hydraulic Access Systems



Non-Pressure Rated Cover



Non-Pressure Rated Cover with Hole



Part Number	Description	Application	Material	Weight
HA700737C25	Non-Pressure Rated Cover without Hole	Intermittent monitoring - chemical injection	Carbon steel	5.4 lbs. (2.5 kg)
HA700738C25	Non-Pressure Rated Cover with 1-1/4" Thru Hole	Continuous monitoring	Carbon steel	5.2 lbs. (2.4 kg)
HA700486C25	Heavy Duty Pressure Rated, Bleed Valve, & Pressure Gauge	Continuous Monitoring - provides a secondary seal (rated for 6000 PSI)	Carbon steel (cover), 316 SS (bleed valve & gauge)	11.5 lbs. (5.2 kg)
HA700487C25	Heavy Duty Pressure Rated Cover, Bleed Valve, Pressure Gauge, & 1/2" NPT Hole	Continuous Monitoring - provides a secondary seal (rated for 6000 PSI)	Carbon steel (cov- er), 316 SS (bleed valve & gauge)	11.5 lbs. (5.2 kg)
HA700489C25	Heavy Duty Pressure Rated Cover without Hole	Intermittent (rated for 6000 PSI)	Carbon Steel	10.5 lbs. (4.8 kg)
HA700490C25	Heavy Duty Pressure Rated Cover with 1/2" NPT Hole	Continuous Monitoring - provides a secondary seal and allows for probe adaptor (rated for 6000 PSI)	Carbon Steel	10.5 lbs. (4.8 kg)
	Heavy Duty Pressure Rated Cover & Bleed Valve	Continuous Monitoring - provides a secondary seal (rated for 6000 PSI)	Carbon steel (cov- er), 316 SS (bleed valve)	10.5 lbs. (4.8 kg)
	Heavy Duty Pressure Rated Cover with Bleed Valve & 1/2" NPT Hole	Continuous Monitoring - provides a secondary seal (rated for 6000 PSI)	Carbon steel (cov- er), 316 SS (bleed valve)	10.5 lbs. (4.8 kg)
	Heavy Duty Pressure Rated Cover with Pressure Gauge & 1/2" NPT Hole	Continuous Monitoring - provides a secondary seal (rated for 6000 PSI)	Carbon steel (cover), 316 SS (gauge)	11.5 lbs. (5.2 kg)